





Features

- AHD & IP Hybrid Design
- Max. recording resolution: 1920 x 1080p
- H.264 video compression
- 8 internal SATA HDD
- 16 Audio & alarm inputs
- Video extraction through network or using USB flash drive
- Video management software with sureSIGHT
- Supporting sureLINK for dynamic IP Internet connection
- iView HD for remote monitoring on mobile phones



Specifications

MODEL		JN6316	
VIDEO INPUT	ANALOG CAMERA	AHD (1080p), AHD (720p), PAL, NTSC	
	NO. OF CHANNEL	16	
	IP CAMERA	TeleEye MP, MQ Series	
	NO. OF CHANNEL	8	
VIDEO OUTPUT	MAIN	DIGITAL VIDEO	1 channel, 1920 x 1080
		VGA	1 channel, 1920 x 1080
RECORDING	MODE	Manual, schedule, motion, event-driven	
	HD TYPE	SATA X 8	
	MAX. RECORDING RATE PER CHANNEL	3MP: 3 fps 1080p: 12 / 15fps 720p: 25 / 30fps	
	PLAYBACK	Play, forward, backward, pause, digital zoom	
COMMUNICATION	NETWORK	RJ-45 10/100 base-T ethernet (auto sensing)	
	CONCURRENT USER	10	
	WEB SERVER	Built-in	
	TELEMETRY CONTROL	RS 485 x 2	
AUDIO	USB	USB2.0 x 2	
	INPUT	RCA X 16	
	OUTPUT	RCA X 1	
EVENT HANDLING	IP CAMERA AUDIO INPUT	8	
	EVENT TYPE	Video motion detection, External alarm, Video loss	
	ACTION TYPE	Local recording, email notification, telemetry preset	
RELAY SWITCH	EXTERNAL ALARM INPUT	16	
	IP CAMERA ALARM INPUT	8	
POWER	NO. OF CHANNEL	1	
	VOLTAGE	110-240V AC	
OPERATING ENVIRONMENT	MAX. RATING	95W	
	AMBIENT TEMPERATURE	-10°C - 50°C	
MECHANICAL DESIGN	RELATIVE HUMIDITY	10% - 90%	
	DIMENSION	430mm (W) x 450mm (D) x 89mm (H)	
	WEIGHT (kg)	10	

www.TeleEye.com

TeleEye Group

Hong Kong Bangladesh China Malaysia
Philippines South Africa Sri Lanka Turkey U.K.

DISTRIBUTED BY: