

Odyssey 5/5E

Grade 3 External Sounders

The Odyssey 5 and Odyssey 5E from Texecom are the ultimate blend of form and function. With stunning low-profile aesthetics the unique mechanical design improves lens contrast, resulting in superior strobe visibility even in direct sunlight.

Available in both twin piezo and single piezo sounder versions, the Odyssey 5 and Odyssey 5E once again define a new benchmark in external sounders.

Outstanding Features

- Maximum Visibility Strobe Housing
- New Captive Screw Fixing Method[†]
- Advanced Microprocessor Technology
- Patented Engineer Hold-off Mode
- Alternating Twin LED Indication
- Polycarbonate Construction
- EN 50131-1 Grade 3

Odyssey 5 External Sounder

- 115 dB Twin Piezo Sounders
- IP65 Sealed Electronics Module
- Wall, Lid & Screw Tamper[†]

Odyssey 5E Economy External Sounder

- 109 dB Single Piezo Sounder
- IP44 Enclosed Electronics Module
- Wall & Lid Tamper[†]



[†]Patent Pending
Odyssey is a trademark of Texecom Limited. (Odys.EU)

Texecom
www.texecom.com

Odyssey 5/5E



A Revolution in Design

Major breakthroughs for the Odyssey 5 lie within the revolutionary mechanical construction. The strobe lens and lid slot into place from above, aiding installation and providing additional benefits. By creating a fully sealed housing, lens contrast is optimised. This serves to maximise the visual impact of the 270 degree strobe when activated, even in bright sunlight. Enhanced security is delivered by the innovative design, providing maximum protection against case tamper.

Odyssey 5E

A cost-effective Odyssey 5E version is also available, featuring the same contemporary styling and major breakthroughs of the Odyssey 5. Aimed at residential installations the Odyssey 5E has a single piezo sounder producing 109dB volume and an adjustable wall & lid tamper switch. The fully enclosed electronics module is protected to IP44 standard.

Patented Engineer Hold-off Mode

Installation and maintenance is made quick, simple and safe by a revolutionary patented safety engineer hold-off mode. On power-up the hold-off mode is automatically enabled, preventing the unit from sounding until the tamper circuit is secure. This enables "one trip up the ladder" installation. Hold-off mode can be re-invoked at any time from the control panel, ensuring easy maintenance and verification.



IP65 Sealed Electronics Module

The advanced electronic module of the Odyssey 5 is protected by a robust inner cover assembly with gasket seal. This maximises protection from dust and moisture, sealing to IP65 rating which enables prolonged exposure to harsher environments without compromising performance or functionality.



Triple Tamper Detection



The captive screw fixing method[†] when combined with a tamper switch, provides the earliest possible indication of unauthorised access to the unit. The fully adjustable wall & lid tamper switch[†] provides maximum flexibility to each installation.

[†]Patent Pending

Low Current Mode



Low current mode is jumper selectable, as with SCB mode it enables a reduction in current drawn from the control panel, to allow installation of additional external sounders. Low current mode maintains significant sounder volume.

European Standards

Safety: Conforms to European Union (EU) Low Voltage Directive (LVD) 73/23/EEC (amended by 93/68/EEC).

EMC: Conforms to European Union (EU) Electro-Magnetic Compatibility (EMC) Directive 89/336/EEC (amended by 92/31/EEC and 93/68/EEC).

Approved to BS EN 55022 Class B and BS EN 50130-4 : 1996.

PD 6662 & EN 50131-1 Grade 3 Environmental Class IV.

The CE mark indicates that this product complies with the European requirements for safety, health, environmental and customer protection.

Texecom products are protected by UK and International patents, trademarks and registered design rights.

UK Registered Design Number 262365.

Odyssey is a trademark of Texecom Limited.

© 2007 Texecom Limited.



Certificate Number: FM 35285



ODY5_EU1